

MOBILE RGB LED Family

Features 0° 60° 120° 180° 240° 300° 360°



RGB MULTI COLORS



21 SCENARIO EFFECTS



HSI



CCT



POWER CONTROL



POWER BANK DC OUTPUT

helping creators BE MORE CREATIVE
Phottix



Phottix M1000R
RGB LIGHT

POWER BANK DC OUTPUT

CRI 96+

132 RED COOLBLUE

132 BLUE COOLBLUE

132 GREEN COOLBLUE

24 W MAX. POWER

Phottix M500R
RGB LIGHT

POWER BANK DC OUTPUT

CRI 96+

90 RED COOLBLUE

90 BLUE COOLBLUE

96 GREEN COOLBLUE

18.5 W MAX. POWER

Phottix M200R
RGB LIGHT

POWER BANK DC OUTPUT

CRI 96+

45 RED COOLBLUE

45 BLUE COOLBLUE

45 GREEN COOLBLUE

10 W MAX. POWER



Technical Specs

SKU / Model	81439 M1000R	81438 M500R	81419 M200R
Color temperature:	3200K - 5600K		
Color model:	0-360° full color control (HSI)		
Brightness range:	1% - 100%		
Max. brightness / illuminance:	3200Lux @ 0.5m (5600K) 750Lux @ 1m (5600K)	2000Lux @ 0.5m (5600K) 550Lux @ 1m (5600K)	1200 Lux @ 0.5m (5600K) 300Lux @ 1m (5600K)
Max. Power:	24W	18.5W	10W
Color rendering index:	CRI 96+ / TLCI 98+		
Battery Capacity:	3.7V 2000mAh	3.7V 1000mAh	3.7V 400mAh
Battery Life: (with 100% power @ 5600K)	about 200min	about 120min	about 90min
Recharging power:	5V 3A USB-C	5V 2A USB-C	5V 2A USB-C
Recharge time:	about 8hrs (5V 2.4A)	about 8hrs (5V 2A)	about 4hrs (5V 2A)
External Output power:	5V 3A (Max) USB / USB-C*	5V 2A USB	5V 2A USB
Dimension:	280 x 180 x 13.7mm	200 x 121 x 13.7mm	151 x 80 x 11.5mm
Weight:	992g	508g	200g

2.1h CCT 3200K 100%

1.4h HSI H:360° S:100%

10h EFFECT B-2 100% Flame 1

3200K - 5600K Color Temperature

Full 0-360° Color Hue & Saturation Adjustment

21 Present Scenario Effects



1. Light stand adaptor use for handle grip*



2. Light stand adaptor use with light stand*
M500R & M1000R RGB Panel only. *