



Light stand adaptor use : 1. for handle grip 2. with light stand (M500R and M1000R only)



1. for M200R
2. for M100R

Adjustable brightness & color temperature

Full 0-360° Color Hue & Saturation Adjustment

21 Present Scenario Effects



MOBILE RGB LED Family

Features 0° 60° 120° 180° 240° 300° 360°

- RGB MULTICOLORES
- 21 SCENARIO EFFECTS
- HSI
- CCT
- POWER CONTROL
- POWER BANK DC OUTPUT



Technical Specs

*The photo display effect and outer covering color of the LED light are for reference only, and the final effect is subject to the actual product!

SKU / Model	81439 M1000R	81438 M500R	81419 M200R	81418 M100R	81401 M5
Color temperature:	3200K - 5600K			2500K - 8000K	6600K (±500K)
Color model:	0-360° full color control (HSI)				
Brightness range:	1% - 100%				5 steps
Max. brightness / illuminance:	3200Lux @ 0.5m (5600K) 750Lux @ 1m (5600K)	2000Lux @ 0.5m (5600K) 550Lux @ 1m (5600K)	1250 Lux @ 0.5m (5600K) 300Lux @ 1m (5600K)	600 Lux @ 0.5m (5600K) 160Lux @ 1m (5600K)	440 Lux @ 0.5m (6600K) 100 Lux @ 1m (6600K)
Max. Power:	24W	18.5W	10W	6.5W	3.5W
Color rendering index:	CRI 96+ / TCLI 98+				90+
Battery Capacity:	3.7V 20000mAh	3.7V 10000mAh	3.7V 4000mAh	3.7V 1500mAh	3.7V 500mAh
Battery Life: (with 100% power @ 5600K)	about 200min	about 120min	about 90min	about 55min	about 42min with 100% power @ 6600K color
Recharging power:	5V 3A USB-C	5V 2A USB-C	5V 2A USB-C	5V 1.3A USB-C	5V 500mA Micro USB
Recharge time:	about 8hrs (5V 2.4A)	about 8hrs (5V 2A)	about 4hrs (5V 2A)	about 2hrs (5V 1.3A)	about 2hrs (5V 500mA)
External Output power:	5V 3A (Max) USB / USB-C	5V 2A USB	5V 2A USB	-	-
Dimension:	280 x 180 x 13.7mm	200 x 121 x 13.7mm	151 x 80 x 11.5mm	110 x 61 x 11.5mm	72 x 41 x 10.5mm
Weight:	992g	508g	200g	117g	44g